

SINGLE WHEEL

m21tt m21tt

Rear single wheels and mixed braking system

Available wheelbases (mm)

M21 tt Single - 2500 (E) / 3360 (H)

M21 tth → Single 2500 (E)

Configuration examples: van, refrigerator, fixed body, tipper and aerial platforms/goods lifts.



Thanks to the 88° opening angle of the doors and the anti-slip step, climbing into the cab is child's play!

DUAL WHEEL

m21t m21tt

Available wheelbases (mm)

M21 t -> 2500 (E) / 2760 (F) / 3360 (H)

M21 tt -> 2500 (E) / 2760 (F) / 3360 (H)

Configuration examples: fixed body, tipper, crane truck, isothermal truck and van.

A new 1.9 engine
 RZ4E -120 hp

• Independent front wheel suspensions

6-speed manual transmission

The entire M21 range features:

- C-section chassis dimensions
 50x180x4 (mm)
 - Front LED lights
- Cab-forward design with 1815 mm cab
 - Class-leading carrying capacity
 - Max towing capacity 3500 kg

m21t vs m21tt

M21 t is our essential high-performance vehicle. 15" wheel rims instead of 16" (max front and rear axle load 1900/2200).

M21 tt is the most fully equipped M21 version: double airbag driver/passenger, glove compartment, passenger sun visor. 16" wheel rims (max front and rear axle load 2100/2435)







HEAVY DIFFERENTIAL FOR HEAVY-DUTY APPLICATIONS

m21th m21th

<u>Larger differential (292 mm instead of 220 mm)</u>
Available wheelbases (mm)

M21th → 2500 (E)/ 2760 (F)

M21 tth -> 3360 (H)

Configuration examples: garbage truck, tipper, fixed body, tow truck and beverage truck.



For further information you can consult our technical sheets on the website www.isuzutrucks.sk







